



LOADING CAPACITIES BEAMS

NEW!

Z BEAMS



ZS/ZM



ZG



ZS/ZM E.P.


MAXIMUM DISTRIBUTED LOAD PER PAIR OF BEAMS IN KG. MAXIMUM DEFLECTION L/200

| MODEL | 0,95m | 1,15m | 1,35m | 1,50m | 1,80m | 1,85m | 2,25m | 2,40m | 2,70m |
|----------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| ZS and ZS/E.P. | 1.102 | 882 | 750 | 674 | 530 | 510 | 368* | 332* | |
| ZM and ZM/E.P. | 1.414 | 1.148 | 966 | 864 | 715 | 692 | 520* | 474* | 402* |
| ZG and ZG/E.P. | 1.606 | 1.286 | 1.092 | 982 | 825 | 790 | 556 | 498 | 406 |

* When using chipboard KIMER recommends using at least 1 reinforcement Z to avoid the lateral movement of the beam (torsion).

NEW!

TUBULAR BEAMS



73 E.P.

MAXIMUM DISTRIBUTED LOAD PER PAIR OF BEAMS IN KG. MAXIMUM DEFLECTION L/200

| MODEL | 0,95m | 1,15m | 1,35m | 1,50m | 1,85m | 2,25m | 2,40m | 2,70m |
|-------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 52/E.P | 1.650 | 1.300 | 1.050 | 950 | 750 | 575 | 525 | 440 |
| 73/E.P | 2.300 | 1.850 | 1.700 | 1.450 | 1.400 | 1.100 | 1.000 | 900 |
| STEP 73/E.P | 2.300 | 2.000 | 1.800 | 1.500 | 1.480 | 1.200 | 1.100 | 1.000 |

NEW!

ROUND TUBE BEAM 30x2mm



ROUND 30x2mm

MAXIMUM DISTRIBUTED LOAD PER PAIR OF BEAMS IN KG. MAXIMUM DEFLECTION L/200

| MODEL | 0,95m | 1,15m | 1,35m | 1,50m | 1,85m | 2,25m | 2,40m | 2,70m |
|--------------|-------|-------|-------|-------|-------|-------|-------|-------|
| Round 30x2mm | 510 | 400 | 315 | 280 | 210 | 120 | 100 | 80 |